



Dimension H:

23 & 30 Degree = 12.67 +/- 0.25 mm (0.499 +/- 0.01 inch)

15 Degree = 12.93 +/- 0.25 mm (0.509 +/- 0.01 inch)

Notes :

1. All dimensions are in millimetres /inches.

2. Epoxy meniscus may extend about 1mm (0.040") down the leads.

## Device Selection Guide


Part Number	Typ. Viewing Angle	Iv (cd) @ 20mA		Standoff Leads	Package Dimension
		Min.	Typ.		
HLMP-CW18-VY0xx	15°	4.20	6.40	No	A
HLMP-CW19-VY0xx	15°	4.20	6.40	Yes	B
HLMP-CW28-TW0xx	23°	2.50	3.80	No	A
HLMP-CW29-TW0xx	23°	2.50	3.80	Yes	B
HLMP-CW38-SV0xx	30°	1.90	3.00	No	A
HLMP-CW39-SV0xx	30°	1.90	3.00	Yes	B

Notes:

1. Tolerance for luminous intensity measurement is +/- 15%
2. The luminous intensity is measured on the mechanical axis of the lamp package.
3. The optical axis is closely aligned with the package mechanical axis.
4. LED light output is bright enough to cause injuries to the eyes. Precautions must be taken to prevent looking directly at the LED with unprotected eyes.

## Part Numbering System

HLMP - C WXX - X X X XX



**Absolute Maximum Ratings (T<sub>A</sub> = 25°C)**

Parameter	Value	Units
DC Forward Current <sup>[1]</sup>	30	mA
Peak Forward Current <sup>[2]</sup>	100	mA
Average Forward Current	30	mA
Power Dissipation	120	mW
LED Junction Temperature	130	°C
Operating Temperature Range	-40 to +85	°C
Storage Temperature Range	-40 to +100	°C
Dip-Drag Solder Temperature <sup>[3]</sup>	260 for 5 secs	°C
Wave Solder Temperature <sup>[3]</sup>	245 for 3 secs	°C

Notes:

1. Derate linearly as shown in Figure 4.
2. Duty Factor 30%, 1 KHz
3. 1.59 mm (0.060 inch) below seating plane

**Electrical/Optical Characteristics (T<sub>A</sub> = 25°C)**

Parameters	Symbol	Minimum	Typical	Maximum	Units	Test Condition
Forward voltage	V <sub>F</sub>		3.4	4.0	V	I <sub>F</sub> = 20 mA
Capacitance	C		53		pF	V <sub>F</sub> =0, f=1 MHz
Reverse Voltage <sup>[1]</sup>	V <sub>R</sub>		0.6		V	I <sub>R</sub> = 10 mA
Thermal resistance	R <sub>qJ-PIN</sub>		240		°C/W	LED Junction to cathode lead
Viewing Angle <sup>[2]</sup>	2q <sub>1/2</sub>				Degree	I <sub>F</sub> = 20 mA
CW18/CW19			15			
CW28/CW29			23			
CW38/CW39			30			
Chromaticity Coordinate <sup>[3]</sup>	X		0.31			I <sub>F</sub> = 20 mA
	Y		0.32			

Notes:

1. The reverse voltage of the product is equivalent to the forward voltage of the protective chip at I<sub>R</sub> = 10 mA
2. 2q<sub>1/2</sub> is the off-axis angle where the luminous intensity is ½ the on axis intensity
3. The chromaticity coordinates are derived from the CIE 1931 Chromaticity Diagram and represent the perceived color of the device.
4. The radiant intensity, I<sub>e</sub> in watts/steradian, may be found from the equation I<sub>e</sub> = I<sub>v</sub>/h<sub>v</sub>, where I<sub>v</sub> is the luminous intensity in candelas and h<sub>v</sub> is the luminous efficacy in lumens/watt.




Figure 1. Relative Intensity vs Wavelength




Figure 2. Forward Current vs Forward Voltage




Figure 3. Relative Iv vs. Forward Current




Figure 4. Maximum Fwd Current vs Temperature







Figure 5. Chromaticity Coordinates Changes over Forward Current



**Figure 6a. CW1x Spatial Radiation Pattern**



**Figure 6b. CW2x Spatial Radiation Pattern**



**Figure 6c. CW3x Spatial Radiation Pattern**

### Intensity Bin Limit Table

Bin	Intensity (mcd) at 20 mA	
	Min	Max
S	1900	2500
T	2500	3200
U	3200	4200
V	4200	5500
W	5500	7200
X	7200	9300
Y	9300	12000

Tolerance for each bin limit is  $\pm 15\%$

### Color Bin Limit Tables


Rank	Limits (Chromaticity Coordinates)				
	1	x y	0.330 0.360	0.330 0.318	0.356 0.351
2	x y	0.287 0.295	0.296 0.276	0.330 0.318	0.330 0.339
3	x y	0.264 0.267	0.280 0.248	0.296 0.276	0.283 0.305
4	x y	0.283 0.305	0.287 0.295	0.330 0.339	0.330 0.360

Tolerance for each bin limit is  $\pm 0.01$

Note:

- Bin categories are established for classification of products. Products may not be available in all bin categories. Please contact your Agilent representative for information on currently available

### Color Bin Limits with Respect to CIE 1931 Chromaticity Diagram



[www.agilent.com/semiconductors](http://www.agilent.com/semiconductors)

For product information and a complete list of distributors, please go to our web site.

Data subject to change.  
 Copyright 2003 Agilent Technologies, Inc.  
 February 23, 2004  
 5989-0461EN