

ADSL-Transformer WSL-A32.326

Specifications



Application
Generic

EP Core Design

EP 13 shown
For smaller sizes down to EP 7,
contact WICKMANN

Features

Optimized magnetic shielding for low interference
High performance, high quality design
Surface Mount and Through Hole package

Packaging

100 pcs./tray
7 trays/carton

Mounting

Through-Hole
For Surface Mount version,
contact WICKMANN

Solderability

270 - 300°C

Isolation voltage

1875 VAC

Operation Temperature Range

-40°C to +85°C



Marking

 Model No.

Unit Weight

7g

Schematics & Mechanicals (mm)



BLACK DOT IS PIN NO.1



WebLinks

Data Sheet

www.wickmann.com/products/WSL_A32326.pdf

Packaging

www.wickmann.com/pack



DC Resistance:	2,4 Ω (1-4) max. ±10%
	2,4 Ω (2-5) max. ±10%
	2,25 Ω (10-6) max. ±10%
	1,80 Ω (9-7) max. ±10%
Open Circuit Inductance:	3,96mH ±5% @ 10kHz, 100mVAC, (1-5), short (2+4)
Leakage Inductance:	18,0μH max.@ 100kHz, 0,1VAC, (1-5), short (2+4, 7+10, 6+9)
Longitudinal Balance:	-
Interwinding Capacity:	60pF max. @ 10kHz, 1,0VAC, (1-9), short (2+4, 7+10)
Reflects 100Ω @ R _L =	-
Insertion Loss:	-
Total Harmonic Distortion (THD):	-

Order Information

Qty.	Order Number
	960 4 632326 9