

# FILTERS

## EDGEPASS FILTER

DiCon's Edgepass Filter is a two-port component that uses a shortpass, longpass, or bandpass filter element to pass and reject wide spectral windows such as the 1310-nm, 1480-nm, 1550-nm, and 1625-nm windows. The component uses a thin-film filter element mounted between a pair of GRIN collimators. DiCon's Edgepass Filter is housed in a compact, environmentally stable package that offers superior resistance to humidity and temperature and is suitable for mounting on a printed circuit board or within a module.



### FEATURES

- Wide selection of broad spectral windows
- Excellent isolation
- Ultra-low insertion loss
- Rugged, environmentally stable package
- Tested to Telcordia GR-1209 and GR-1221

### APPLICATIONS

Edgepass Filters enhance wavelength isolation in broadband WDM systems. They can be used to isolate optical time domain reflectometer (OTDR) signals from transmission signals in active fiber monitoring systems.




# FILTERS

## SPECIFICATIONS<sup>1</sup>

Insertion loss	0.6 dB typ., 0.8 dB max.
Isolation	45 dB min.
Back-reflection	-50 dB max.
PDL	0.05 dB typ., 0.1 dB max.
Thermal stability	0.005 dB/°C max.
Fiber type	9/125 Corning SMF-28
Operating temperature	0°C to +65°C
Storage temperature	-40°C to +85°C
Humidity	85°C/85%RH/14 days

1. All specifications referenced without connectors.

## HOUSING DIMENSIONS



Units: mm

## ORDERING INFORMATION

Transmission Band <sup>1,2</sup>		BFC -	-	-	-	-
13	1260.0 - 1360.0 nm					
15	1530.0 - 1570.0 nm					
13/15	1260.0 - 1570.0 nm					
16	1610.0 - 1660.0 nm					
15/16	1530.0 - 1660.0 nm					
Rejection Band <sup>1,2</sup>						
13	1260.0 - 1360.0 nm					
15	1530.0 - 1570.0 nm					
13/15	1260.0 - 1570.0 nm					
16	1610.0 - 1660.0 nm					
15/16	1530.0 - 1660.0 nm					
Connector Type						
FC	FC/SPC					
FC/APC	FC/APC					
FC/UPC	FC/UPC					
SC	SC/SPC					
SC/APC	SC/APC					
SC/UPC	SC/UPC					
ST	ST/SPC					
ST/UPC	ST/UPC					
LC	LC/UPC					
N	None					
Fiber Jacket						
2	250 micron, 200 kpsi bare fiber					
9	900 micron, tight buffer					
Pigtail Length						
1	1 meter					
X	Specify X meters					

1. All wavelengths referenced to vacuum.  
2. Transmission and rejection bands must not overlap.

## SPECTRAL PERFORMANCE

