



Security & Chip Card ICs

SLE 44C80S

8-bit Security Controller with
17-Kbyte ROM, 256 byte RAM
8 Kbyte EEPROM and Sleep Mode

This document contains preliminary information on a new product under development. Details are subject to change without notice.

Revision History: Current Version 10.01

Previous Releases: 07.99

Page	

<p>Important: Further information is confidential and on request. Please contact: Infineon Technologies AG in Munich, Germany, Security & Chip Card ICs, Tel +49 - (0)89 234-80000 Fax +49 - (0)89 234-81000 E-Mail: security.chipcard.ics@infineon.com</p>
--

Edition 2001

Published by Infineon Technologies AG, CC Applications Group
St.-Martin-Strasse 53, D-81541 München
© Infineon Technologies AG 2001
All Rights Reserved.

Attention please!

The information herein is given to describe certain components and shall not be considered as warranted characteristics.

Terms of delivery and rights to technical change reserved.

We hereby disclaim any and all warranties, including but not limited to warranties of non-infringement, regarding circuits, descriptions and charts stated herein.

Infineon Technologies is an approved CECC manufacturer.

Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office in Germany or our Infineon Technologies Representatives world-wide (see address list).

Warnings

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office.

Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

8-bit Security Controller with 17-Kbyte ROM, 256-byte RAM, 8-Kbyte EEPROM and Sleep Mode

Features

- 8-bit microcomputer in CMOS technology
- Instruction set opcode compatible with standard SAB8051 processor
- Software compatible with SLE 44C80
- Dedicated, non-standard architecture with execution time less than half of standard SAB 8051 processor
- 15-Kbyte User ROM for application programs
- 2-Kbyte manufacturer ROM for **Chip Management System (CMS)**
- **8-Kbyte EEPROM** as program/data memory
- 256-byte RAM
- Power saving sleep mode
- Clock freq. = int. freq.:
 - 1 to 5 MHz¹⁾ at 5 V ± 10 %,
 - 1 to 4 MHz at 3 V ± 10 %
- Contact configuration and serial interface in accordance with ISO7816
- Supply voltage range: 2.7 V to 5.5 V
- < 10 mA supply current at 5 MHz
- Temperature range: – 25 to + 70 °C²⁾
- ESD protection larger than 4 kV

Document References

- Confidential Data Book SLE 44CxxS
- Instruction Set SLE44CxxS – Quick Reference
- Qualification report
- Chip delivery specification for wafer with chip-layout (die size, orientation,...)
- Module specification containing description of package, etc.
- Qualification report module

Development Tools Overview

- Short Product Information Software Development Kit SDK CC

EEPROM

- Reading, erasing and writing byte by byte
- Flexible page mode for 1 to 32 bytes write/erase operation
- 32 bytes security area
- Write time 3.5 ms, erase time 1.75 ms
- Frequency-adaptable programming time
- Minimum of 500,000 write/erase cycles³⁾
- Data retention for minimum of ten years
- EEPROM programming voltage generated on chip

Security Features

- ROM code not visible due to implantation
- Low voltage sensor
- High voltage sensor
- Low-frequency sensor
- High-frequency protection
- 16 bytes security PROM, hardware protected
- Unique chip identification number for each chip

CMS

- Intelligent write/erase routines for N bytes programming (0 < N < 256)
- **Two serial interface modes according to ISO 7816-3:**
 - 9600 bit/s related to 3.57 MHz
 - 9600 bit/s related to 4.91 MHz

Support

- HW-& SW-Tools (Emulator, Card Emulator, Simulator)
- Application notes

Supported Standards

- ISO/IEC 7816
- EMV 2000
- GSM 11.1x
- ETS I TS 102 221

¹⁾ Extended frequency range up to 7.5 MHz is available, see ordering information.

²⁾ Extended temperature range is available for certain applications, e.g. GSM, see ordering information

³⁾ Values are temperature dependent for further information please refer to your Infineon Technologies Sales Officer.

Ordering Information

Type	Package ¹	Voltage Range	Temperature Range	Frequency Range
SLE 44C80S-M4	M4	2.7 V - 5.5 V	– 25°C to + 70°C	1 MHz - 5 MHz @ 5V 1 MHz – 4 MHz @ 3V
SLE 44C80S -C	C			
SLE 44C80S -T85-M4	M4	2.7 V - 5.5 V	– 25°C to + 85°C	1 MHz - 5 MHz @ 5V 1 MHz – 4 MHz @ 3V
SLE 44C80S -T85-C	C			
SLE 44C80S -V5-M4	M4	4.5 V - 5.5 V	– 25°C to + 70°C	1 MHz - 5 MHz
SLE 44C80S -V5-C	C			
SLE 44C80S -V5-T85-M4	M4	4.5 V - 5.5 V	– 25°C to + 85°C	1 MHz - 5 MHz
SLE 44C80S -V5-T85-C	C			
SLE 44C80S -V5-F7-M4	M4	4.5 V - 5.5 V	– 25°C to + 70°C	1 MHz - 7.5 MHz
SLE 44C80S -V5-F7-C	C			

Production sites:

- Regensburg SLE 44CxxS
- UMC Taiwan SLE 44CxxU

¹ available as wire-bonded module (M4) for embedding in plastic cards or as die (C) for customer packaging

Pin Description




Figure 1 Pin Configuration (top view)

Pin Definitions and Functions

Card Contact	Symbol	Function
C1	VCC	Operating voltage
C2	RST	Reset input
C3	CLK	Processor clock input
C5	GND	Ground
C4;C6,C8	N.C.	Not connected
C7	I/O	Bi-directional data port

General Description

SLE 44C80S is a member of the Infineon Technologies 44 security microcontroller family, especially designed for smart card applications. The device is fabricated in an Infineon Technologies proprietary CMOS technology, resulting in a significant reduction of die size compared to the SLE 44C80S. New features such as low voltage operation, extended page mode and I/O routines offer additional performance required in applications like 3V SIM cards for GSM, payment, pay-TV or security access while maintaining software compatibility to the SLE 44C80S manufactured in the previous technology.