




18/19 LED Cluster, 15mm SC Bayonet Based Lamps

Packages	Replaces Incandescent	Part Number	Input Voltage	Power Watts (typ)	Intensity per LED I_v mod (typ)	λ_p (nm)	View Angle $2\theta^{1/2}$	Custom Options
<p>660nm Ultra Red GaAlAs/GaAlAs</p>	309,311, 1383,1384, 1723, 3011	B618-0UR-014N	12/14V	1.0W to 1.7W	2000	660	12° to 15°	Replace N in part number with required viewing angle S - Standard (25° to 30°) M - Medium (45° to 50°) W - Wide (120° to 125°)
		B618-0UR-024N	24V					
		B618-0UR-028N	28V					
		B618-0UR-036N	36V					
<p>633nm Super Red InGaAlP</p>	309,311, 1383,1384, 1723, 3011	B618-0ER-014N	12/14V	1.0W to 1.7W	3500	630	12° to 15°	Replace N in part number with required viewing angle S - Standard (25° to 30°) M - Medium (45° to 50°) W - Wide (120° to 125°)
		B618-0ER-024N	24V					
		B618-0ER-028N	28V					
		B618-0ER-036N	36V					
<p>612nm Super Orange InGaAlP</p>	309,311, 1383,1384, 1723, 3011	B618-0UO-014N	12/14V	1.0W to 1.7W	6500	612	12° to 15°	Replace N in part number with required viewing angle S - Standard (25° to 30°) M - Medium (45° to 50°) W - Wide (120° to 125°)
		B618-0UO-024N	24V					
		B618-0UO-028N	28V					
		B618-0UO-036N	36V					
<p>595nm Super Yellow InGaAlP</p>	309,311, 1383,1384, 1723, 3011	B618-0UY-014N	12/14V	1.0W to 1.7W	5500	595	12° to 15°	Replace N in part number with required viewing angle S - Standard (25° to 30°) M - Medium (45° to 50°) W - Wide (120° to 125°)
		B618-0UY-024N	24V					
		B618-0UY-028N	28V					
		B618-0UY-036N	36V					
<p>4500K Incandescent White SiC/GaN</p>	309,311, 1383,1384, 1723, 3011	B618-0IW-014N	12/14V	1.0W to 1.7W	2000	4500K	12° to 15°	Replace N in part number with required viewing angle S - Standard (25° to 30°) M - Medium (45° to 50°) W - Wide (120° to 125°)
		B618-0IW-024N	24V					
		B618-0IW-028N	28V					
		B618-0IW-036N	36V					
<p>8000K Cool White SiC/GaN</p>	309,311, 1383,1384, 1723, 3011	B618-0CW-014N	12/14V	1.0W to 1.7W	6000	8000K	12° to 15°	Replace N in part number with required viewing angle S - Standard (25° to 30°) M - Medium (45° to 50°) W - Wide (120° to 125°)
		B618-0CW-024N	24V					
		B618-0CW-028N	28V					
		B618-0CW-036N	36V					
<p>570nm Lime Green InGaAlP</p>	309,311, 1383,1384, 1723, 3011	B618-0UG-014N	12/14V	1.0W to 1.7W	1000	570	12° to 15°	Replace N in part number with required viewing angle S - Standard (25° to 30°) M - Medium (45° to 50°) W - Wide (120° to 125°)
		B618-0UG-024N	24V					
		B618-0UG-028N	28V					
		B618-0UG-036N	36V					
<p>525nm Aqua Green SiC/GaN</p>	309,311, 1383,1384, 1723, 3011	B618-0AG-014N	12/14V	1.0W to 1.7W	10,000	525	12° to 15°	Replace N in part number with required viewing angle S - Standard (25° to 30°) M - Medium (45° to 50°) W - Wide (120° to 125°)
		B618-0AG-024N	24V					
		B618-0AG-028N	28V					
		B618-0AG-036N	36V					
<p>505nm Blue Green SiC/GaN</p>	309,311, 1383,1384, 1723, 3011	B618-0BG-014N	12/14V	1.0W to 1.7W	2000	505	12° to 15°	Replace N in part number with required viewing angle S - Standard (25° to 30°) M - Medium (45° to 50°) W - Wide (120° to 125°)
		B618-0BG-024N	24V					
		B618-0BG-028N	28V					
		B618-0BG-036N	36V					
<p>470nm Super Blue SiC/GaN</p>	309,311, 1383,1384, 1723, 3011	B618-0PB-014N	12/14V	1.0W to 1.7W	3000	470	12° to 15°	Replace N in part number with required viewing angle S - Standard (25° to 30°) M - Medium (45° to 50°) W - Wide (120° to 125°)
		B618-0PB-024N	24V					
		B618-0PB-028N	28V					
		B618-0PB-036N	36V					
		B619-0UR-120AN	120VAC					
		B619-0ER-120AN	120VAC					
		B619-0UO-120AN	120VAC					
		B619-0UY-120AN	120VAC					
		B619-0IW-120AN	120VAC					
		B619-0CW-120AN	120VAC					
		B619-0UG-120AN	120VAC					
		B619-0AG-120AN	120VAC					
		B619-0BG-120AN	120VAC					
		B619-0PB-120AN	120VAC					


Viewing Angle:
12° to 15°



Narrow Angle (N)


Optional Viewing Angles:

25 to 30




Standard Angle (S)

45 to 50



Medium Angle (M)

120 to 125




Wide Angle (W)

Notes:


- Not all possible combinations of voltage, intensity and angle are available
- Intensity shown is for narrow angle. Intensity is reduced 12 to 15 times when using extra wide angles

InfraReds

850/880/940nm



Dimensions



Low Cost Specials

- 8000K Cool White PN Example: B618-1CW-120AN
- 525nm Aqua Green PN Example: B618-1AG-120AN
- 505nm Blue Green PN Example: B618-1BG-120AN
- 470nm Super Blue PN Example: B618-1PB-120AN

Options: (Baseless with 12" wire leads)

Series: L618/L619

PN Example: L618-0UO-014N

