

Features

2 Meg x 8 bit CMOS Static

Random Access Memory

- Access Times 20 thru 35ns
- TTL Compatible Inputs and Outputs
- Fully Static, No Clocks

High Density Packaging

- JEDEC Approved, Revolutionary Pinout
- 36 Pin DIP, No. 178

Single +5V ($\pm 10\%$) Supply Operation

2 Megabits x 8 Static RAM CMOS, Module with Revolutionary Pinout


The EDI8F82046C is a 16 Megabit CMOS Static RAM based on four 512Kx8 Static RAMs mounted on a multi-layered epoxy laminate (FR4) substrate.

The EDI8F82046C is packaged in a 36 pin DIP and features the JEDEC approved, revolutionary pinout.

All inputs and outputs are TTL compatible and operate from a single 5V supply.


Fully asynchronous, the EDI8F82046C requires no clocks or refreshing for operation. 1Megx8 Static RAM CMOS, Module

Pin Configurations and Block Diagram



Pin Names

A0-A20	Address Inputs
\overline{E}	Chip Enable
\overline{W}	Write Enable
\overline{G}	Output Enable
DQ0-DQ7	Common Data Input/Output
VCC	Power (+5V $\pm 10\%$)
VSS	Ground
NC	No Connection



Electronic Designs Incorporated

• One Research Drive • Westborough, MA 01581 USA • 508-366-5151 • FAX 508-836-4850 •
Electronic Designs Europe Ltd. • Shelley House, The Avenue • Lightwater, Surrey GU18 5RF
 United Kingdom • 01276 472637 • FAX: 01276 473748

Absolute Maximum Ratings*

Voltage on any pin relative to VSS	-0.5V to 7.0V
Operating Temperature TA (Ambient)	
Commercial	0°C to +70°C
Industrial	-40°C to +85°C
Storage Temperature	-55°C to +125°C
Power Dissipation	3.0 Watt
Output Current	20 mA

*Stress greater than those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions greater than those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

Recommended DC Operating Conditions

Parameter	Sym	Min	Typ	Max	Units
Supply Voltage	VCC	4.5	5.0	5.5	V
Supply Voltage	VSS	0	0	0	V
Input High Voltage	VIH	2.2	--	6.0	V
Input Low Voltage	VIL	-0.3	--	0.8	V

AC Test Conditions

Input Pulse Levels	VSS to 3.0V
Input Rise and Fall Times	5ns
Input and Output Timing Levels	1.5V
Output Load	1TTL = 30pF

(note: For TEHQZ, TGHOZ and TWLQZ, CL = 5pF)

DC Electrical Characteristics

Parameter	Sym	Conditions	Min	Typ*	Max	Units
Operating Power	ICC1	$\bar{W}, \bar{E} = VIL, I/O = 0mA,$ Min Cycle	--	350	430	mA
Supply Current						
Standby (TTL) Power	ICC2	$\bar{E} \geq VIH, VIN \leq VIL$ $VIN \geq VIH$	--	110	190	mA
Supply Current						
Full Standby Power	ICC3	$\bar{E} \geq VCC-0.2V$ $VIN \geq VCC-0.2V$ or $VIN \leq 0.2V$	--	20	30	mA
Supply Current (CMOS)						
Input Leakage Current	ILI	$VIN = 0V$ to VCC	--	--	±10	µA
Output Leakage Current	ILO	$V I/O = 0V$ to VCC	--	--	±10	µA
Output High Voltage	VOH	$IOH = -4.0mA$	2.4	--	--	V
Output Low Voltage	VOL	$IOL = 8.0mA$	--	--	0.4	V

*Typical: TA = 25°C, VCC = 5.0V

Truth Table

\bar{G}	\bar{E}	\bar{W}	Mode	Output	Power
X	H	X	Standby	High Z	ICC2, ICC3
H	L	H	Output Deselect	High Z	ICC1
L	L	H	Read	DOUT	ICC1
X	L	L	Write	DIN	ICC1

Capacitance

(f=1.0MHz, VIN=VCC or VSS)

Parameter	Sym	Max	Unit
Address Lines	CI	30	pF
Data Lines	CD/Q	43	pF
Chip Enable Line	CC	10	pF
Write and Output Enable Lines	CW	32	pF


These parameters are sampled, not 100% tested.

AC Characteristics Read Cycle


Parameter	Symbol		20ns		25ns		35ns		Units
	JEDEC	Alt.	Min	Max	Min	Max	Min	Max	
Read Cycle Time	TAVAV	TRC	20		25		35		ns
Address Access Time	TAVQV	TAA		20		25		35	ns
Chip Enable Access Time	TELOV	TACS		20		25		35	ns
Chip Enable to Output in Low Z (1)	TELOX	TCLZ	3		3		3		ns
Chip Disable to Output in High Z (1)	TEHOZ	TCHZ		10		12		15	ns
Output Hold from Address Change	TAVQX	TOH	3		3		3		ns
Output Enable to Output Valid	TGLOV	TOE		8		10		12	ns
Output Enable to Output in Low Z (1)	TGLOX	TLOZ	0		0		0		ns
Output Disable to Output in High Z (1)	TGHOZ	TOHZ		8		10		12	ns

Note 1: Parameter guaranteed, but not tested.


Read Cycle 1 - \bar{W} High, \bar{G} , \bar{E} Low



Read Cycle 2 - \bar{W} High



Write Cycle 2 - \bar{E} Controlled




Ordering Information

Standard Power	Speed (ns)	Package No.
ED18F82046C20M6C	20	178
ED18F82046C25M6C	25	178
ED18F82046C35M6C	35	178

To order an Industrial grade product substitute the letter C in the Suffix with the letter I, eg. ED18F82046C25M6C becomes ED18F82046C25M6I.

Package Description

Package No. 178
36 Pin Dual-in-line Package



Electronic Designs Incorporated

• One Research Drive • Westborough, MA 01581USA • 508-366-5151 • FAX 508-836-4850 •
Electronic Designs Europe Ltd. • Shelley House, The Avenue • Lightwater, Surrey GU18 5RF
United Kingdom • 01276 472637 • FAX: 01276 473748

Electronic Designs Inc. reserves the right to change specifications without notice. CAGE No. 66301