



BVB-D6512-A

DESCRIPTION


Dice Material : GaP/GaP Yellow Green

Light Color : Green Color


Reflector Color : White Color

PACKAGE CONFIGURATION

Tolerance : ± 0.2 mm



TYPICAL INTERNAL EQUIVALENT CIRCUIT



ABSOLUTE MAXIMUM RATINGS AT Ta = 25 °C

PARAMETER	MAX.	UNIT
Power Dissipation	0.7	W
DC Forward Current	150	mA
Reverse Voltage	8	V
Operating Temperature Range	-20 °C to + 70 °C	
Storage Temperature Range	-30 °C to + 80 °C	

ELECTRICAL / OPTICAL CHARACTERISTICS AT Ta = 25 °C

SYMBOL	PARAMETER	TEST COND.	MIN.	TYP.	MAX.	UNIT
V _F	Forward Voltage	I _F = 100 mA		4.0	4.5	V
I _R	Reverse Current	V _R = 8 V			2.0	mA
λ _p	Peak Emission Wavelength	I _F = 100 mA		567		nm
λ _d	Dominant Wavelength	I _F = 100 mA		572		nm
I _V	Luminous Intensity	I _F = 100 mA	85	125		cd/m ²
	Luminous Uniformity	I _F = 100 mA		30	50	%

*Bright View reserves the rights to alter specifications and remove availability of products at any time without notice.