




A 形外壳尺寸




B 形外壳尺寸



B-4形外壳尺寸



B-5形外壳尺寸



技术参数:

工作电压:

7-30Vdc(6.5/8/12mm传感器)
5-40Vdc(18mm传感器)
7-40Vdc(30mm传感器)

最大波纹:

10%

空载电流:

10mA

电压降:

1.5V

工作温度:

-25-70

最大温度漂移:

± 10%

重复精度:

2%

开关迟滞:

10%

防护等级:

IP67

开关状态显示

黄色LED

电缆内芯截面积:

0.22mm²(6.5/8mm传感器)

0.34mm²(12/18mm传感器)

0.50mm²(30mm传感器)

短路及过载保护:

有

反向连接保护

有

电脉冲抑制(EMC):

符合EN60947-5-2

允许冲击和震动:

符合IEC68-2-27IEC68-2-6

材质:

电缆:

2m PVC CE120-2211; 90 ; 300V; 0.R

6.5/8mm传感器:

不锈钢

12/18/30mm传感器:

黄铜镀镍

感应面:

塑料




直径	M8x1	M12x1	M18x1	M30x1.5
螺 型号	SW13	SW17	SW24	SW36
母 厚度	4mm	4mm	4mm	5mm
最大扭矩	10Nm	15Nm	35Nm	80Nm

外形类型	齐 非 平 平	L1	L2	L3	L4	L5	电 缆 直 径	外 壳 直 径	感 应 距 离	频 率	工 作 电 流	型号及接线图	
		mm	mm	mm	mm	mm						PNP常开	PNP常闭
A		--	30	--	--	30	3.5	6.5	1.5	4	200	IH06-OPY-F1,5C/St	IH06-CPY-F1,5C/St
A		5	25	--	--	30	3.5	6.5	2.5	3	200	IH06-OPY-N2,5C/St	IH06-CPY-N2,5C/St
B		--	30	--	--	30	3.5	M8x1	1.5	4	200	IM08-OPY-F1,5C/St	IM08-CPY-F1,5C/St
B		5	25	--	--	30	3.5	M8x1	2.5	3	200	IM08-OPY-N2,5C/St	IM08-CPY-N2,5C/St
B-4		--	30	--	--	30	4	M12x1	2	2	200	IM12-OPY-F002C/St	IM12-CPY-F002C/St
B-4		7	23	--	--	30	4	M12x1	4	1.5	200	IM12-OPY-N004C/St	IM12-CPY-N004C/St
B-5		--	30	--	--	30	5	M18x1	5	0.8	200	IM18-OPY-F005C/St	IM18-CPY-F005C/St
B-5		10	20	--	--	30	5	M18x1	8	0.6	200	IM18-OPY-N008C/St	IM18-CPY-N008C/St
B-5		--	35	--	--	35	6	M30x1.5	10	0.8	200	IM30-OPY-F010C/St	IM30-CPY-F010C/St
B-5		15	20	--	--	35	6	M30x1.5	15	0.4	200	IM30-OPY-N015C/St	IM30-CPY-N015C/St

注:表格中所列型号为PNP型,把中间字母"P"改为"N"即为NPN型

NPN常开



NPN常闭

