



# T-5/8 Surface Mounting Tape & Reel Package, 0581, 0587, 0589 J Series for low current or superbright use



The 058X series of tape and reel packaged subminiature lamps are designed for automated surface mount applications. The different series indicate lead shaping from the same LED type. When packaged in bulk without lead forming the series is 0580. These lamps are compatible with vapor phase reflow surface mounting as well as conventional soldering. Available on 1Kpc or 5Kpc reels.



## GENERAL INFORMATION

Operating Temperature Range	-40 °C to +85 °C
Storage Temperature Range	-40 °C to +85 °C
Lead Soldering Temperature	240 °C for 3 sec
Preheat Temperature	100 °C

Part No.	Emitted Color	Peak		Absolute Maximum Ratings					E/O Characteristics					
		(nm)	(nm)	Pd (mW)	If (mA)		Ir @Vr=5V (µA)	Vr (V)	Iv (mcd) @If=20mA			Vf (V) @ If=20mA		2 1/2 (Deg)
					dc	1/10 duty @ 1 kHz			2mA	Min	Typ	Min	Typ	
JEC058X	Red	632	20	60	25	160	10	5	25	172	418	2.0	2.4	30
JGC058X	Green	575	20	60	25	160	10	5	10	115	172	2.0	2.4	30
JYC058X	Yellow	591	15	60	25	160	10	5	26	172	430	2.0	2.4	30
JOC058X	Orange	621	18	60	25	160	10	5	26	172	430	2.0	2.4	30
JRC058X	OrRed	639	20	60	25	160	10	5	20	160	338	2.0	2.4	30
JYOC058X	YelOrng	611	17	60	25	160	10	5	26	172	430	2.0	2.4	30

Specifications subject to change without notice. Dimensions are in mm±0.3 unless stated otherwise.

IDEA, Inc., 1300-B Pioneer St., Brea, CA 92821

Ph:562-697-4332, 800-LED-IDEA; Fax: 562-690-1352 011S-J058X